

1583A Paired - DataTwist® Category 5e

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Color Code Chart : No. 8 for DataTwist Cables (Modified Western Electric).pdf</p>
---	--

Description:

4 Pair UTP, 200MHz Category 5e, Vertical Tray Rated, 24 AWG Solid Bare Copper, Polyolefin Insulation, PVC Jacket, Rip Cord, Sequential Marking at Two Foot Intervals

SUITABLE APPLICATIONS:

Suitable Applications Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PO - Polyolefin
---------------------	-----------------

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.195 in.
--------------------------	----------

1583A Paired - DataTwist® Category 5e

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
Bulk Cable Weight	29 lbs/1000 ft.
Max. Recommended Pulling Tension	35 lbs.
Min. Bend Radius (Install)	0.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM, UL444
CEC/C(UL) Specification	CM
IEC Specification	11801 Category 5
TIA/EIA Specification	568-B.2 Category 5e
Other Specification	NEMA WC-63.1 Category 5e, UL verified to Category 5e

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
CSA Flame Test	FT1

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	1585A

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	330 pF/100 m
Nominal Velocity of Propagation	70 %
Maximum Delay (ns/100 m)	538 @ 100MHz ns/100 m
Maximum Delay Skew (ns/100m)	45 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9.38 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	3 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :

1583A Paired - DataTwist® Category 5e

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	65.3	62.3	63.0	60.0	20.0	23.0
4	4.1	56.3	53.3	51.0	49.0	23.0	23.0
8	5.8	51.8	48.8	46.0	43.0	24.5	24.5
10	6.5	50.3	47.3	43.0	41.0	25.0	25.0
16	8.2	47.3	44.3	39.0	36.0	25.0	25.0
20	9.3	45.8	42.8	36.5	33.5	25.0	25.0
25	10.4	44.3	41.3	33.9	30.9	24.3	24.3
31.25	11.7	42.9	39.9	31.0	28.0	23.6	23.6
62.5	17.0	38.4	35.4	22.0	19.0	21.5	21.5
100	22.0	35.3	32.3	14.0	11.0	20.1	20.1
155	28.1	32.5	29.5	4.4	1.4	15.8	
200	32.0	30.8	27.8	4.0	1.0	15.0	

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.8	60.8
4	100 ± 15	100 ± 15	51.7	48.7
8	100 ± 15	100 ± 15	45.7	42.7
10	100 ± 15	100 ± 15	43.8	40.8
16	100 ± 15	100 ± 15	39.7	36.7
20	100 ± 15	100 ± 15	37.7	34.7
25	100 ± 15	100 ± 15	35.8	32.8
31.25	100 ± 15	100 ± 15	33.9	30.9
62.5	100 ± 15	100 ± 15	27.8	24.8
100	100 ± 15	100 ± 15	23.8	20.8
155	100 ± 25	100 ± 15	19.9	16.9
200	100 ± 25	100 ± 15	17.7	14.7

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1583A 0021000	4 PR #24 PP FR PVC	1000	21	RED	C
1583A 002U1000	4 PR #24 PP FR PVC	U1000	21	RED	
1583A 0031000	4 PR #24 PP FR PVC	1000	21	ORANGE	C
1583A 003U1000	4 PR #24 PP FR PVC	U1000	21	ORANGE	
1583A 0041000	4 PR #24 PP FR PVC	1000	21	YELLOW	C
1583A 004U1000	4 PR #24 PP FR PVC	U1000	21	YELLOW	
1583A 0051000	4 PR #24 PP FR PVC	1000	21	GREEN, DARK	C

1583A Paired - DataTwist® Category 5e

1583A 005U1000	4 PR #24 PP FR PVC	U1000	21	GREEN, DARK	
1583A 0061000	4 PR #24 PP FR PVC	1000	21	BLUE, LIGHT	C
1583A 0061640	4 PR #24 PP FR PVC	1640	34.44	BLUE, LIGHT	
1583A 0063000	4 PR #24 PP FR PVC	3000	63	BLUE, LIGHT	C
1583A 006U1000	4 PR #24 PP FR PVC	U1000	21	BLUE, LIGHT	
1583A 0091000	4 PR #24 PP FR PVC	1000	21	WHITE	C
1583A 0093000	4 PR #24 PP FR PVC	3000	63	WHITE	C
1583A 009U1000	4 PR #24 PP FR PVC	U1000	21	WHITE	
1583A 0101000	4 PR #24 PP FR PVC	1000	21	BLACK	C
1583A 010U1000	4 PR #24 PP FR PVC	U1000	21	BLACK	
1583A 0121000	4 PR #24 PP FR PVC	1000	21	PINK	C
1583A 012U1000	4 PR #24 PP FR PVC	U1000	21	PINK	
1583A F6H1000	4 PR #24 PP FR PVC	1000	21	GRAY, DARK PEARL	C
1583A F6H1640	4 PR #24 PP FR PVC	1640	34.44	GRAY, DARK PEARL	
1583A F6H3000	4 PR #24 PP FR PVC	3000	63	GRAY, DARK PEARL	C
1583A F6HU1000	4 PR #24 PP FR PVC	U1000	21	GRAY, DARK PEARL	

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 07-28-2004

© 2004 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.